

LESELI REFLECTOR downlight



- * LED source integrated in downlight luminaries.
- * Connection to mains with screw terminals.
- * Well distributed light output, ideal for the general lighting of the ambient.
- * Thermally conductive PC body; extremely light and manageable
- * Complete with springs for easy fastening on false ceilings.
- * Internal power supply.
- * Working Temperature: -20°C +35°C.
- * White bezel.
- * IP20 VI - IP43 VO

Item Characteristics

Code	D41530A
Lamp Voltage	220-240 V
Nominal Power	15 W
Base	cavi/wires
Lamp Current	0,073 A
Nominal Flux	1100 LUMEN
Light Tonality	Warm white
Colour temperature	3000 K
Opening beam	70°
Diameter	150 mm
Lenght	81 mm
Weight	255 g

Performance

Axis cd	900
Photometry	D41530A
Irc/Ra	80
Lifetime	25000 h
Energy Class	A
kWh/1000h	15

Tech Info


Dimmable	NO
Number of ON-OFF cycles	100000
Power Factor	0,95
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C

Fulfilled Directives and norms

2006/95/CE * Bassa Tensione 2004/108/CE *
 Compatibilità Elettromagnetica 2011/65/UE *
 RoHS 2012/19/UE * RAEE EN 61547 * anno
 2010 EN 55015 * anno 2014 EN 61000-3-2 *
 anno 2007 EN 61000-3-2/A1/A2 * anno 2011
 EN 61000-3-3 * anno 2014 EN 60598-1 EN
 60598-2-2 2010/30/EU * Energy Consumption
 874/2012 * Regulation for Energy Labelling

Spectrocolorimetry and Photometry

3000K Ra80		H(m)	D(m)	E _{max} (lx)
Fixture Power	15W		73°	
Source Flux	1300lm	1	1.49	949
Fixture Flux	1300lm	2	2.98	237
Efficacy	87lm/W	3	4.47	105
		4	5.96	59
I _{max}	949cd	5	7.45	38



Eulumdat file for lighting calculations available on the website

Shipping info

Item barcode	8011905854867
Pack	6 pz
Master barcode	8011905854942