

LESELI SLIM downlight



- * Extremely limited recessed fixtures with only 26mm, ideal for recessed lighting in walls, ceilings and furnishings where space is limited.
- * Well diffused light output, ideal for the general lighting of the ambient.
- * Die-cast aluminium body and plastic screen: extremely light and manageable.
- * Remote driver 68x34x22mm thick;
- * Complete with springs for easy fastening on false ceilings.
- * Working Temperature: -25°C +35°C.
- * White ring.
- * IP43

Item Characteristics

Code	D41540SL2
Lamp Voltage	220-240 V
Nominal Power	6 W
Base	cavi/wires
Input current	0,056
Lamp Current	0,05 A
Nominal Flux	420 LUMEN
Rated Flux	0 LUMEN
Input voltage	220-240
Light Tonality	Natural white
Colour temperature	4000 K
Opening beam	120°
Diameter	128 mm
Lenght	26 mm
Weight	128 g
Maximum output current (mA)	0,115 mA

Performance

Axis cd	120
Photometry	D41540SL2
Irc/Ra	>80
Lifetime	25000 h
Energy Class	A+
kWh/1000h	6

Tech Info

Dimmable	NO
Number of ON-OFF cycles	100000
Power Factor	0,52
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.


T (°C) Working environment Temp.

-25°C / +35°C

Fulfilled Directives and norms

2009/125/EC * Ecodesign 1194/2012 *
 Regulation for Ecodesign 2015/1428 *
 Regulation for Ecodesign 2010/30/EU * Energy
 Labelling 874/2012 * Regulation for Energy
 Labelling 2011/65/EU * RoHS 2012/19/EU *
 RAEE 2014/30/EU * EMC (Compatibilità
 Elettromagnetica) 2014/35/EU * LVD (Bassa
 Tensione) CEI EN 55015:2014 (+A1:2016)
 CEI EN 60598-1:2015 (+EC:2015/+EC:2016)
 CEI EN 60598-2-2:2012 CEI EN 61000-3-
 2:2015 CEI EN 61000-3-3:2014 (+EC:2014)
 CEI EN 61547:2010 CEI EN 62031:2009
 (+A1/+A2:2015) CEI EN 62471:2010 IEC/TR
 62471-2:2009 CEI 34-141:2014

Spectrocolorimetry and Photometry



4000K Ra80		H(m)	D(m)	Emax(lx)
Fixture Power	6W		129°	
Source Flux	420lm	1	4.22	119
Fixture Flux	420lm	2	8.43	30
Efficacy	70lm/W	3	12.65	13
Imax	119cd	4	16.87	7
		5	21.09	5

Eulumdat file for lighting calculations available on the website

Shipping info

Item barcode	8011905860912
Pack	10 pz
Master barcode	8011905863593