

LESELI SLIM downlight



- * Extremely limited recessed fixtures with only 26mm, ideal for recessed lighting in walls, ceilings and furnishings where space is limited.
- * Well diffused light output, ideal for the general lighting of the ambient.
- * Die-cast aluminium body and plastic screen: extremely light and manageable.
- * Remote driver 68x34x22mm thick;
- * Complete with springs for easy fastening on false ceilings.
- * Working Temperature: -25°C +35°C.
- * White ring.
- * IP43

Item Characteristics

Code	D82540QSL2
Lamp Voltage	220-240 V
Nominal Power	18 W
Base	Cavi / Wire
Input current	0,087
Lamp Current	0,15 A
Nominal Flux	1400 LUMEN
Rated Flux	0 LUMEN
Input voltage	220-240
Light Tonality	Natural white
Colour temperature	4000 K
Opening beam	120°
Diameter	202 mm
Lenght	202 mm
Lenght 1	26 mm
Weight	300 g
Maximum output current (mA)	0,350 mA

Performance

Axis cd	390
Photometry	D82540QSL2
Irc/Ra	>80
Lifetime	25000 h
Energy Class	A+
kWh/1000h	18

Tech Info

Dimmable	NO
Number of ON-OFF cycles	100000
Power Factor	0,52
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0

LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2009/125/EC * Ecodesign 1194/2012 * Regulation for Ecodesign 2015/1428 * Regulation for Ecodesign 2010/30/EU * Energy Labelling 874/2012 * Regulation for Energy Labelling 2011/65/EU * RoHS 2012/19/EU * RAEE 2014/30/EU * EMC (Compatibilità Elettromagnetica) 2014/35/EU * LVD (Bassa Tensione) CEI EN 55015:2014 (+A1:2016) CEI EN 60598-1:2015 (+EC:2015/+EC:2016) CEI EN 60598-2-2:2012 CEI EN 61000-3-2:2015 CEI EN 61000-3-3:2014 (+EC:2014) CEI EN 61547:2010 CEI EN 62031:2009 (+A1/+A2:2015) CEI EN 62471:2010 IEC/TR 62471-2:2009 CEI 34-141:2014

Spectrocolorimetry and Photometry

4000K Ra80		H(m)	D(m)	Emax(lx)
Fixture Power	18W		131°	
Source Flux	1400lm	1	4.36	389
Fixture Flux	1400lm	2	8.73	97
Efficacy	78lm/W	3	13.09	43
Imax	389cd	4	17.46	24
		5	21.82	16



Eulumdat file for lighting calculations available on the website

Shipping info

Item barcode	8011905860943
Pack	10 pz
Master barcode	8011905861742