

SLIMFLUX ROUND SURFACE PANEL 60 - DIMMABLE



* SLIMFLUX ROUND 60 installation possibilities: with recessed driver or surface mounting (the panel remains 43 mm away from the mounting surface).

- * Immediate switch-on.
- * Maintenance-free.
- * Extremely high color rendering: Ra>80.
- * White painted metal body.
- * Can be used with TRIAC dimmers.
- * Class I fittings.

Item Characteristics

Code	LP60TNW
Nominal Power	35 W
Base	cavi/wires
Input current	500
Nominal Flux	3000 LUMEN
Input voltage	220-240
Light Tonality	Natural white
Colour temperature	4000 K
Diameter	600 mm
Lenght	12 mm
Lenght 1	55 mm
Weight	4420 g
Maximum output current (mA)	840 mA
Output load (W)	35 W

Performance

Photometry	LP60TNW
Irc/Ra	>80
Lifetime	40000 h
Energy Class	A

Tech Info

Dimmable	YES
Number of ON-OFF cycles	100000
Power Factor	0,9
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C

Fulfilled Directives and norms 2006/95/CE * Bassa Tensione 2004/108/CE * Compatibilità Elettromagnetica 2011/65/UE * RoHS 2012/19/UE * RAEE EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3-2 * anno 2007 EN 61000-3-2/A1/A2 * anno 2011 EN 61000-3-3 * anno 2014 EN 60598-1 EN 60598-2-2 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling

Spectrocolorimetry and Photometry

 850661 Imax=347cd/klm	4000K Ra80		H(m)	D(m)	Emax(lx)
	Fixture Power	35W			113°
Source Flux	3000lm		1	3.03	1042
Fixture Flux	3000lm		2	6.06	261
Efficacy	86lm/W		3	9.09	116
Imax	1042cd		4	12.12	65
			5	15.15	42

Eulumdat file for lighting calculations available on the website

Shipping info

Item barcode	8011905850661
Pack	1 pz