



DURALUX S


Typology

Compact, circular and linear fluorescent lamps.

Features

The best fluorescent and triphosphorous powders for maximum light colour control and light emission over time, good colour rendering and the excellent luminous efficiency.

A wide reliable range for installation in professional contexts such and home environments.



Characteristic data

Power	11 W	Beam	320°	Dimmable	No	Input	90,4 Vac
Base	G23	IP	20	Flux	900 lm	Tc	2700 K
Ra	>80						

Dimensional characteristics



Ø	34 mm
H	237 mm


Lighting and photometric features

Beam opening	320°
Flux	900 lm
CCT nominal colour temperature	2700 K
Colour of the light	Homelight
Colour rendering index	>80
Lifespan	10000 h
Mercury	2,5 mg
Luminous Flux Maintenance at 2000h	93
Luminous Flux Maintenance at 4000h	90
Luminous Flux Maintenance at 6000h	88
Luminous Flux Maintenance at 8000h	85
Luminous Flux Maintenance at 12000h	81
Luminous Flux Maintenance at 16000h	80
Lamp survival factor at 2000h	100
Lamp survival factor at 4000h	95
Lamp survival factor at 6000h	80
Lamp survival factor at 8000h	60
Lamp survival factor at 10000h	50
Lamp survival factor at 12000h	45

Electrical characteristics

Rated power	11 W
Input voltage	90,4 Vac
Frequency	50 Hz
Dimmable	No
Input current	0.152 A
Weighted energy consumption	14 kWh/1000h
Operating temperature	-15°C / +35°C
Equivalence with incandescent lamp	70
Operating position	360°

Spectrometry



Standards and Directives

2009/125/EC, 245/2009, 347/2010, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863	CEI EN 61000-3-2:2019
CEI EN 55015:2020	CEI EN 61000-3-3:2014
CEI EN 60968:2016	CEI EN 61547:2010

Logistics data

Number of pieces multiple pack	50
Barcode multiple pack	8011905742829