



DIMMER DMX FOR DURASTRIP HiVOLT

Dimmer DMX for DURASTRIP HiVolt.

Can be used with ZKTPC; 300 W/CH, 3 CH.



Characteristic data

Input	220-240 Vac	Base	Screws	IP	20	LED Warranty	G3
-------	-------------	------	--------	----	----	--------------	----

Dimensional characteristics

L	170 mm
H	29 mm
L2	59 mm

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50 Hz
Output voltage	220-240
Operating temperature	-25°C / +35°C

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61347-1:2016
2014/35/EU, 2015/863	CEI EN 61347-2-11:2011
CEI EN 55015:2020	CEI EN 61347-2-11/A1:2019
CEI EN 61000-3-2:2019	CEI EN 61547:2010

Logistics data

Item net weight	164 gr
Barcode single item	8011905862473