

NEW ARRIVALS



LAUNCH PROMO -10%*
until Sept. the 30th

LESELI DOWNLIGHT SC

TYPE

LED source with SMD technology and high efficiency chip integrated into a recessed luminaire.

CHARACTERISTICS

Soft satin effect polycarbonate anti-glare diffuser. Flicker Free.

MOUNTING

Complete with springs for easy fastening into false ceilings. Cable (1 m) with IP65 quick connector.

MATERIALS

Thermally conductive body; extremely light and manageable.

- **FOUR WATTAGES: 6W - 12W - 22W - 30W**
- **THREE COLOUR TEMPERATURES: 3000K - 4000K - 6000K**
- **25.000H L70B20**
- **RA>80**
- **FLICKER FREE**
- **STANDARD CUTTING HOLES: 75 - 150 - 195 mm**
- **LIGHTWEIGHT THERMO-CONDUCTIVE PLASTIC BODY**
- **BEAM ANGLE: 110°**
- **FLUX: FROM 450 TO 2600LM**
- **BUILT-IN DRIVER EXCEPT 30W ITEM WITH REMOTE DRIVER**

W	art.	W	lm	cd	K	PF	▲	∅	H	ⓘ	📦
6	DT30L130	6	455	160	3000	0,8	110°	92	50	75	40
	DT30L140	6	470	165	4000	0,8	110°	92	50	75	40
	DT30L160	6	470	165	6000	0,8	110°	92	50	75	40
12	DT40L130	12	1000	350	3000	0,9	110°	166	54	150	20
	DT40L140	12	1050	365	4000	0,9	110°	166	54	150	20
	DT40L160	12	1050	365	6000	0,9	110°	166	54	150	20
22	DT80L130	22	2000	700	3000	0,9	110°	216	58	195	10
	DT80L140	22	2050	715	4000	0,9	110°	216	58	195	10
	DT80L160	22	2050	715	6000	0,9	110°	216	58	195	10
30	DT80L1HP30	30	2600	910	3000	0,9	110°	216	58	195	10
	DT80L1HP40	30	2600	910	4000	0,9	110°	216	58	195	10
	DT80L1HP60	30	2600	910	6000	0,9	110°	216	58	195	10

now in stock

* Discount as free goods to be added in the same purchase order and for the codes of this promotion. Items in this family can also be purchased individually (subject to the general minimum order).

