



LAUNCH PROMO -10%*
until Sept. the 30th

VALO MINI

TYPE

Low thickness, small size LED downlights.

CHARACTERISTICS

Compact and easy to install. Tilt Adjustability 30°. Special design of the lens ensures excellent light beam diffusion. Non removable internal power supply.

MOUNTING

Complete with springs for easy fastening into false ceilings.

MATERIALS

Heat resistant, anti-yellowing plastic body.

- **WATTAGE: 7W**
- **ADJUSTABLE**
- **TWO COLOUR TEMPERATURES: 3000K - 4000K**
- **15.000H L70B30**
- **RA>80**
- **TWO SHAPES: ROUND AND SQUARE**
- **LOW THICKNESS: 40 mm**
- **STANDARD CUT-OUT REPLACEMENT FOR OLD DICHROICS**
- **BODY IN ROBUST PLASTIC MATERIAL**
- **BEAM ANGLE: 40°**
- **FLUX: 620/650 LM**
- **BUILT-IN DRIVER**



| art. | W | lm | cd | K | | L | L1 | H | | | |
|-----------|---|-----|-----|------|-----|----|----|----|-------|----|----|
| VA03L130Q | 7 | 620 | 700 | 3000 | 40° | 90 | 90 | 40 | 75x75 | 83 | 10 |
| VA03L140Q | 7 | 650 | 735 | 4000 | 40° | 90 | 90 | 40 | 75x75 | 83 | 10 |

* Minimum Order Quantity



| art. | W | lm | cd | K | | ∅ | H | | | |
|-----------|---|-----|-----|------|-----|----|----|----|----|----|
| VA03L130T | 7 | 620 | 700 | 3000 | 40° | 90 | 40 | 72 | 80 | 10 |
| VA03L140T | 7 | 650 | 735 | 4000 | 40° | 90 | 40 | 72 | 80 | 10 |

* Minimum Order Quantity

* Discount as free goods to be added in the same purchase order and for the codes of this promotion.

now in stock

[go to page](#)