





RTF100 New

Wide range of PRO recessed luminaires with a soft design, well diffused light, very high colour rendering and long service life.

Can be used everywhere:

Offices: common areas, corridors, meeting rooms

Hospitality sector: hotels, restaurants

Production areas: general lighting, functional areas

Retail shops: general lighting, can be modulated by area

depending on the wattage chosen.

Residential: from small wattages in warm colours to larger wattages in stairwell areas etc.

- THREE WATTAGES: 7W 14W 24W
- THREE COLOUR TEMPERATURES: 3000K 4000K 6000K
- 50,000H L80B20
- RA>90
- TWO SHAPES: ROUND AND SQUARE
- LOW THICKNESS: 24 26 35 MM
- STANDARD CUTTING HOLES: 75 120 225 MM
- STURDY ALUMINIUM BODY
- 110° APERTURE
- LUMENS FROM 660 TO 2400LM
- REMOTE DRIVER INCLUDED
- POSSIBILITY OF DIMMING WITH DELT40D-M DIMMABLE DRIVER CODE
- CAN BE CONNECTED WITH KTEMR03 BACK-UP LIGHTING KIT (3 HOURS' LIGHTING TIME)

W	art. ROUND	lm	cd		art. SQUARED	lumen	cd		K	PF	
7	RTF03L130T	600	290	75	RTF03L130Q	630	310	75x75	3000	0,5	110°
	RTF03L140T	630	305	75	RTF03L140Q	665	325	75x75	4000	0,5	110°
	RTF03L160T	660	320	75	RTF03L160Q	700	340	75x75	6000	0,5	110°
14	RTF04L130T	1195	585	120	RTF04L130Q	1260	615	120x120	3000	0,5	110°
	RTF04L140T	1260	615	120	RTF04L140Q	1325	645	120x120	4000	0,5	110°
	RTF04L160T	1325	645	120	RTF04L160Q	1390	675	120x120	6000	0,5	110°
24	RTF08L130T	2185	965	195	RTF08L130Q	2185	965	195x195	3000	0,95	110°
	RTF08L140T	2300	1015	195	RTF08L140Q	2300	1015	195x195	4000	0,95	110°
	RTF08L160T	2415	1065	195	RTF08L160Q	2415	1065	195x195	6000	0,95	110°

now in stock